

K-Series STAINLESS STEEL HOUSING

Model: **KA-DGR PANEL** for KB-DAR, KC-DAR

INSTALLATION MANUAL

PACKAGE CONTENTS

- **KA-DGR PANEL**
- Screws pack (3 pcs)
- Screwdriver
- Camera frame

MOUNTING


(See illustration below)

- 1. Pull out and down on screw cover at the bottom of K(B,C)-DAR.
- 2. Loosen tamperproof screw with hexagonal wrench.
- 3. Separate door station from back frame.

KA-DGR PANEL is a surface mount box made of stainless steel

for KB-DAR and KC-DAR color video door stations.

- On bottom of unit, press two tabs with a screwdriver to unlock front cover panel.
- 5. Loosen tamperproof screw further, and remove it and the entire front panel. (See "REMOVE FRONT COVER PANEL" at the bottom of this page for further clarification.)
- 6. Mount the back frame to a single gang box, placing stainless steel mounting bracket between the gang box and mounting frame.
- 7. Mount door station to the back frame with supplied screw.
- 8. Place supplied stainless steel camera frame onto camera section.
- 9. Attach stainless steel cover with tamperproof screws (supplied).



REMOVE FRONT COVER PANEL(*)

- (*) Entire gray front panel must be removed.
- Loosen tamperproof screw with supplied wrench.
- 2. Press tabs on the bottom of the K(B,C)-DAR with screwdriver to unlock gray front panel.
- Loosen the tamperproof screw further until it can be removed.
- Remove and discard the gray front panel and the tamperproof screw of the K(B,C)-DAR.

